



215.00 EUR  
incl. 19% VAT, plus [shipping](#)

Support:  [Specifications \[EN\]](#)

- INTEL® Cedar Trail-M Processor N2600 + NM10 Chipset
- Support 1 \* DDR3 800MHz Single CH up to 2GB
- Support DirectX 9 Graphics up to 640MHz
- Support 1 \* Serial ATAII (3Gb/s) Devices
- Support Dual Gigabit LAN
- Support DVI-I Output
- Equipped with 802.11 b/g/n WiFi card & Internal Antenna (JBC362F36W-2600-B only)
- Support 2.5" SATA HDD
- Support Mini PCI-E socket
- Support CFast card socket

<b>CPU</b>	INTEL® Cedar Trail-M Processor N2600 (1.6GHz) INTEL® Cedar Trail-M Processor N2800 (1.86GHz)
<b>Chipset</b>	INTEL®NM10 Express chipset
<b>Memory</b>	1 * DDR3 800MHz Single CH SO-DIMM up to 2GB (For Cedar Trail-M N2600) 1 * DDR3 1066MHz Single CH SO-DIMM up to 4GB (For Cedar Trail-M N2800)
<b>Expansion Slots</b>	1 * MINI PCI-E
<b>Storage</b>	1 * Serial ATAII 3Gb/s connectors 1 * CFast card socket
<b>Audio</b>	Realtek ALC662 HD Audio CODEC with 4-Channel
<b>Ethernet LAN</b>	2 * RTL8111E PCI-EVL Gigabit LAN
<b>USB</b>	Embedded 7 * USB 2.0/1.1
<b>LVDS</b>	Onboard 1 * 24-bits Dual channel & 1 * 18-bits Single LVDS connectors 4 * USB 2.0/1.1 ports 2 * RJ-45 ports
<b>Rear Panel I / O</b>	Line-out port 1 * DVI-I port 1 * 12V DC-IN JACK

**Internal I / O**

2 \* USB 2.0 header for 3 \* USB 2.0 ports

1 \* Audio header

System/Chassis/NB Fan Connectors

1 \* GPIO header

1 \* CFast card reader socket

DIY switch x2 (reset & power button)

4 \* COM header (COM1~3 for RS232, COM4 for RS232/422/485)

**BIOS**

AMI 16MB SMT Flash ROM

**Form Factor**

3.5" SBC form factor (148mmx102mm)

**Certificate**

CE,FCC,RoHS,ERP

**Functional**

ATM, Automation, Medical Equipment, Security, General Application, Transportation, Digital Signage,  
Kiosk, POS machine, LCD TV PC, Embedded Fanless application

**Temperature**

Operating within 0~60 centigrade

Storage within -20-85 centigrade

**Product Accessories**

- DVI-I to CRT Converter
- Manual
- CD
- 1x SATA cable
- SATA power cable
- 4x COM cable