



2069.00 EUR

incl. 19% VAT, plus [shipping](#)



- Intel® Kabylake-U Series SoC Processor
- Support ITPS power supply (9~36V DC-in)
- 8 \* PoE ports

|             |                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MB Model    | <ul style="list-style-type: none"> <li>– JNF752-7100U (Core i3) / (TDP 15W)</li> <li>– JNF752-7200U / 7300U (Core i5) / (TDP 15W)</li> <li>– JNF752-7600U (Core i7) / (TDP 15W)</li> </ul> <p>The model will be ordered according to the CPU purchase status, and the detailed situation is recommended to contact the sales.</p>                                                                                       |
| Part No     | <ul style="list-style-type: none"> <li>– HBF752-7100-B (non-WIFI)/HBF752W-7100-B (WIFI)</li> <li>– HBF752-7200-B (non-WIFI)/HBF752W-7200-B (WIFI)</li> <li>– HBF752-7300-B (non-WIFI)/HBF752W-7300-B (WIFI)</li> <li>– HBF752-7600-B (non-WIFI)/HBF752W-7600-B (WIFI)</li> </ul> <p>The model will be ordered according to the CPU purchase status, and the detailed situation is recommended to contact the sales.</p> |
| BIOS        | – AMI Flash ROM                                                                                                                                                                                                                                                                                                                                                                                                         |
| CPU/Chipset | – Intel® Kabylake-U Core-i SoC Processor                                                                                                                                                                                                                                                                                                                                                                                |
| Memory      | – Support 2 * DDR4 2133MHz SO-DIMM slots up to 32GB                                                                                                                                                                                                                                                                                                                                                                     |
| Storage     | <ul style="list-style-type: none"> <li>– Support 2 * 2.5" SATA Device tray (Removable hard drive)</li> <li>– Support 1 * Mini-PCIe slot (full size, only for mSATA)</li> </ul>                                                                                                                                                                                                                                          |
| Network     | – 1 * Intel® i219LM & 1 * Intel® i210AT GbE                                                                                                                                                                                                                                                                                                                                                                             |
| Expansion   | <ul style="list-style-type: none"> <li>– 2 * Mini PCIe (full-size, for WiFi/3G/4G/ Capture Card module expansion)</li> <li>– 1 * Mini-PCIe slot (USB only, full size, for 4G LTE + GPS expansion)</li> </ul>                                                                                                                                                                                                            |

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rear Panel I/O  | <ul style="list-style-type: none"> <li>– 4 * USB 2.0, 4 * USB 3.0</li> <li>– 1 * HDMI (Max. resolution:4096 x 2304@24Hz)</li> <li>– 1 * VGA (Max. resolution:1920 x 1080@60Hz)</li> <li>– 2 * RJ45, 8 * 1000M PoE (23W/per port)</li> <li>– 1 * Line-out, 1 * MIC</li> <li>– 2 * COM (RS232/RS422/RS485)</li> <li>– 1 * DC 9~36V_3PIN Industrial connector, 1 * DC 48~52V_2PIN Industrial connector</li> <li>– 1 * Clear COMS Button</li> <li>– 1 * AT Mode setting_2PIN Industrial connector</li> <li>– 2 * Antenna holes (Optional)</li> </ul> |
| Front Panel I/O | <ul style="list-style-type: none"> <li>– 1 * Power Button + LED, 1 * Reset Button, 1 * HDD LED</li> <li>– 1 * Power on-off_2PIN Industrial connector</li> <li>– 2 * COM (RS232)</li> <li>– 2 * GPIO (1*DI &amp; 1*DO/ 6 BIT) (Support Isolated)</li> <li>– 1 * LVDS out (Max. resolution:1920 x 1080@60Hz)</li> <li>– 3 * SIM card holes</li> <li>– 2 * 2.5" SATA Device tray (Easy to change HDD)</li> <li>– 1 * GND Hold</li> <li>– 1 * CAN Bus (DB9 Type_Optional)</li> <li>– 3 * Antenna holes (Optional)</li> </ul>                         |
| Power Source    | <ul style="list-style-type: none"> <li>– DC 9~36V INPUT for SYSTEM (Support Boot &amp; Shutdown delay function_ITPS)</li> <li>– DC 48~52V INPUT for POE LAN</li> </ul>                                                                                                                                                                                                                                                                                                                                                                           |
| Compliance      | – CE, FCC, LVD, RoHS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Temperature     | <ul style="list-style-type: none"> <li>– Operating Temperature: -20 ~ 70° C</li> <li>– Storage Temperature: -20 ~ 70° C</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                               |
| Dimensions      | – 232 (W) x 231.4 (D) x 103 (H) mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Packing         | <ul style="list-style-type: none"> <li>– Net Weight: 2.7KG</li> <li>– Gross Weight: 3.7KG</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| OS Support      | – Windows 10, Linux                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Warranty        | – 2 Years limited warranty                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |