

609.00 EUR

 incl. 19% VAT, plus [shipping](#)


- Intel Comet Lake-S !
- H410 Chipset !
- 19" Enclosure !

**Support:**  [Datasheet](#)

- Intel® 10th LGA1200 Socket Comet Lake-S Processor (Max. 65W TDP)
- Support 2\* DDR4 2666/2400MHz SO-DIMM up to 64 GB
- 3\* USB3.2, 3\* USB2.0, 4\* COM, 1\* HDMI, 1\* DP, 2\* RJ45, 1\* MIC, 1\* Line out, 1\* Line in
- M/B Form Factor : Mini ITX (170x170mm)
- 1U 250W FLEX Power

|               |   |                      |  |
|---------------|---|----------------------|--|
| Dimensions    | – 330 (W) x 192 (D) x 44 (H) mm   |                      |  |
| MB model      | – MI08-00 / Mini ITX (6.7-in * 6.7-in, 170 * 170mm) (Default)<br>– MI08-02 (W/TPM2.0)   |                      |  |
| Part No       | Non-Wifi  | Wifi                 |  |
|               | – HBJC150I08-H410-B   | – HBJC150I08I-H410-B |  |
| CPU/Chipset   | – Intel® 10th LGA 1200 Socket Core i7/i5/i3/Pentium/Celeron Comet Lake-S Processor (Max. 65W TDP)<br>– H410 chipset   |                      |  |
| BIOS          | – AMI 128Mb Flash ROM   |                      |  |
| Memory        | – 2* Dual CH non-ECC DDR4 2666/2400MHz SDRAM SO-DIMM up to 64GB   |                      |  |
| Network       | – 1 * Intel i219V GbE<br>– 1 * Intel i211AT GbE   |                      |  |
| Storage       | – 2 * 2.5" or 1 * 3.5" SATA3 6Gb/s internal drive bay<br>– 1 * M.2_SSD (M key-2242/2280) support NVMe   |                      |  |
| Expansion     | – 1* M.2 E-key 2230 (PCIex1/USB2.0)<br>– 1* PCIex16 slot<br>– Support onboard TPM2.0 (MI08-02) / optional   |                      |  |
| Rear I/O Port | – 3 * USB 3.2 (Gen. 1)<br>– 1* USB 2.0<br>– 1 * HDMI 1.4 (Max Resolution: 4096x2160@30Hz)<br>– 1 * DP (Max Resolution: 4096x2304@60Hz)<br>– 2 * RJ45<br>– 1 * Mic, 1 * Line in, 1 * Line-out<br>– 4 * COM (COM 1 support RS232/422/485) |                      |  |

|                |   |
|----------------|---|
| Front I/O Port | - 1 * Power button, 1 * Reset button<br>- 1 * Power LED, 1 * HDD LED<br>- 2 * USB 2.0                                       |
| Power Source   | - 1U 250W FLEX POWER<br>- AC 90~240V input  |
| Certification  | - CE, FCC, LVDS, RoHS   |
| Environment    | - Operating Temperature : 0°C~50°C<br>- Storage Temperature : -10°C~70°C<br>- Humidity: 10% ~ 90% RH @40°C (non-condensing) |
| Packing        | - Net Weight■3.5 KG<br>- Gross Weight■4.5 KG<br>- Color Box Dimension■560(W) x 400(D) x 140(H) mm                           |
| Warranty       | -2 Year limited warranty  |